

Masoneilan* Valve Aware* Service - Baker Hughes • GE Mark* Vle Control System • AMS™ From Emerson Process Management™ (AMS OPC Server Required) (3) • PRM® From Yokogawa® Corporation (3) • PKS® From Honeywell® Corporation (Jun 6th, 2024Masoneilan 37/38 Series - Baker Hughes57 Machine Screw Stainless Steel 70 Ball & Retainer1 Stainless Steel 1. Size 13, 15, 18 And 24 Only. Reverse - Type 38 Ref. No. Description Materials 15 Gasket (Packing Box) Copper 17 Yoke Cast Iron 18 Cap Screw Carbon Steel 19 Gasket Acrylic Fiber 20 Packing Nut Brass 21 Snap Ring Carbon Steel 22 Actuator Apr 15th, 2024Supplier Quality Requirements - Baker HughesAll BH Suppliers Need To Go Through The On-boarding Process - As Required By BH Quality Management System Procedures To Be Issued A Global Supplier Listing - Number (GSL). 3.1.2. Steps For Supplier On-Boarding May Include The Following: A) Jun 11th, 2024.

Masoneilan 12400 Series - Baker HughesLow Level Alarm High Level Alarm Each Discrete Contact Is Configurable For Normal Open Or Closed Action And With Several Possible Triggers. HART® Analog Output Analog Output Main 4-20 MA Level Variable (Transmitter) Or Controller Output (Controller) With HART® Data Second 4-20mA Level Va Apr 1th, 2024Consolidated 1541/1543 Series - Baker HughesSpindle ASTM A108 1213 Carbon Steel 6 Spindle Assembly (G And H Orifice) Spindle Collar ASTM A582 416 Cond. T Stainless Steel Spindle ASTM A108 1213 Carbon Steel 7 Spring Washer ASTM A108 1213 Carbon Steel 8 Spring Alloy Steel 9 Cap Brass/Commercial Grade Brass 10 Compression Screw ASTM Mar 14th, 2024Consolidated 1511 Series - Baker HughesSpindle ASTM A108 Grade 1213 CS Spindle Collar ASTM A276 Type 410 Condition T St. St. 10 Spindle Assembly (N-Q Orifice) Spindle Head ASTM A108 Grade 1020 CSI Spindle Stem ASTM A108 Grade 1020 CS Roll Pin Carbon Steel 11 Spring Washer (H - L Orifice) ASTM A108 Grade 1020 CSI Spring Washer (M - Q Orific May 7th, 2024.

Masoneilan 21000 Series - Baker HughesCryogenic Extension Seat Leakage IEC 60534-4 And ANSI/ FCI 70.2 Class Standard Bonnet Extension Bonnet Inch Mm Min. Max. Min. Max. Min. Max. 0.75 To 8 20 To 200 ASME Class 150 To 2500 And Equivalent PN Metal PTFE, LE Or LE FireSafe Packing-20°F (-29°C) +450°F (+ Jun 7th, 2024

There is a lot of books, user manual, or guidebook that related to Baker Hughes Announces January 2013 Rig Counts PDF in the link below:

[SearchBook\[OC85\]](#)